(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 3 March 2005 (03.03.2005)

(10) International Publication Number WO 2005/019649 A1

- (51) International Patent Classification7: 23/02
- F04B 49/025.
- (21) International Application Number:

PCT/EP2004/009405

- (22) International Filing Date: 23 August 2004 (23.08.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

MI2003A 001662


22 August 2003 (22.08.2003)

- (71) Applicant (for all designated States except US): ASKOLL HOLDING S.R.L. [IT/IT]; Via Industria, 30, I-36031 Povolaro di Dueville (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): MARIONI, Elio [IT/IT]; Via Molino, 6, I-36031 Dueville (IT).

- (74) Agents: BOTTI, Mario et al.; Botti & Ferrari S.r.l., Via Locatelli, 5, I-20124 Milano (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: IMMERSION PUMP EQUIPPED WITH A FLOAT CONTROL DEVICE



(57) Abstract: The present invention relates to a synchronous pump structure, particularly to an immersion pump (1) equipped with a float control device (3) and comprising a synchronous electric motor (2) with a permanent magnet rotor (8). The pump (1) is so structured that the float (16) of the control device (3) is incorporated in an envelope (11), externally associated with the body (15) of the pump (1). A sensor element (4) of the control device (3) housed in the pump body (15) in correspondence with the float (16) is also provided.

WO 2005/019649 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments